

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Calsullence 152 WR
Grease

Calsullence 152 WR Grease

Greases

Description

Calsullence 152 WR is a calcium sulfonate complex thickened lubricating grease based on mineral oil. The grease contains antioxidants and corrosion inhibitors.

This functional soap gives the product excellent load carrying capacity, making it suitable for heavily loaded applications. It also has excellent mechanical stability, good corrosion protection and water resistance.

Application

Calsullence 152 WR is suitable for industrial, marine and off road applications. The extreme load carrying capacity and excellent water resistance make the product suitable for heavily loaded applications in hot or wet and corrosive environments.

Performance Level

ISO 129424: L-XC(F)DIB2

DIN 51502: KP2N-30

Benefits

- Excellent resistance to shock loads
- Very good corrosion protection
- Very good water resistance

Typical Inspection Data

Appearance	Smooth Grease
Colour	Brown
NLGI classification	2
Thickener	Calcium sulfonate complex
Base oil	Mineral oil
Water resistance at 90°C	1
Water spray off	40%

Water washout @ 79 °C	
Worked penetration	265-295
Dropping Point (IP396)	>280°C
Copper corrosion (IP112)	pass
Emcor salt water	
Four ball weld load kgs	7500 N
Flow pressure at -30°C	
Operating temperature range	-30°C to +140 °C (max + 180°C)

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.