

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Delta 5w/40 C3

Delta 5w/40 C3

Low SAPS Fully Synthetic Engine Oils

Description

Revolution Delta 5w-40 is a long life, fully synthetic low SAPS SAE 5w-40 passenger car engine oil for normal and extended drain intervals. This oil is suitable for VW, Audi, Seat, Skoda and Ford diesel engines, including those fitted with VW505.01 pumpe Duse (PD) diesel injector systems.

Application

Revolution Delta 5w-40 an engine oil developed to enable outstanding performance along with full compatibility with on board emissions systems and DPFs. This ensures minimal pollution to the environment.

Performance Level

- API SCF
- ACEA C3
- MB 229.51&229.31
- BMW LL-04
- VW 502.00/505.01
- Porsche A40
- GM Dexos 2
- Ford WSS-M2C917-A
- B71-2297

Benefits

- Viscosity remains stable during total service of the oil for optimum engine protection

- Low SAPS engine oil protects exhaust gas after-treatment system
- Reduces fuel consumption
- Extended drain interval capability
- High oil film strength under all engine operating conditions
- Excellent engine performance at all driving conditions
- Outstanding protection against foam formation, rust and corrosion

Typical Inspection Data

Kinematic Viscosity @ 40°C (cSt)	92
Kinematic Viscosity @ 100°C (cSt)	14.2
Viscosity Index	159
TBN (mg KOH/g)	8.5
Pour Point (°C)	-42
Flash Point (°C)	230

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.