

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk www.q8oils.co.uk

sales@revolutionoil.co.uk enquiries@revolutionoil.co.uk

Registered in England & Wales No.4356026

VAT Reg No. GB 815 3964 16



Technical Data Sheet

Semi Synthetic Two Stroke Engine Oil





Semi Synthetic Two Stroke Engine Oil

Two Stroke Oils

Description

Revolution Semi Synthetic Two Stroke Engine Oil is specifically designed for excellent protection and cleanliness in two stroke engines. It guarantees superior control against the blocking of the exhaust system and reduces exhaust smoke.

Application

Revolution Semi Synthetic Two Stroke Engine Oil is suitable for both oil injection and premix systems. It is particularly reccommended for garden machinery and scooters.

Performance Level

- API TC
- JASO FC
- ISO-L-EGC

Benefits

- Excellent engine efficiency and power
- Good self mixing properties
- Reduced exhaust smoke
- Reduces exhaust blockages
- Excellent engine protection and cleanliness for enclosed engines

Typical Inspection Data

Kinematic Viscosity @ 40° (cSt)	68
Kinematic Viscosity @ 100° (cSt)	9.16
Viscosity Index	130
Pour Point Degrees Centigrade	-22
Flash Point Degrees Centigrade	134
Density @ 15 Degrees Centigrade	863





"In line with our policy of continued improvement	t, Revolution Oil Ltd reserves the right to change s	specification and availability without prior notice. E and O E.*
---	--	--