

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Soluble Cutting Oil NP

Soluble Cutting Oil NP

Soluble Cutting Fluid

Description

Revolution Soluble Cutting Fluid is a concentrate with superb stability when mixed with water at typically 3%-10% concentration levels. High oil content cutting fluid concentrate which incorporates an excellent bio stability package giving a high quality, milky emulsion for most metalworking applications requiring a non E.P. performance fluid. It can, however be used at stronger dilution rates dependent on application.

This product has a unique corrosion inhibition system to provide levels of corrosion protection not normally available from milky soluble products, hence providing good machine tool protection, both on slideways and the general working area, with the added benefits of finished component protection.

Application

Suitable for most machining applications. This product should always be added to water to form the most stable emulsion. No added silicones. Soluble cutting fluids should always be stored inside and away from frosty conditions or direct sunlight.

Benefits

- Resistant to tramp oil
- Helps keep machine clean/no sticky residue
- Low foam
- Good work piece visibility
- General purpose/versatile
- Excellent corrosion protection
- Long sump life

Typical Inspection Data

	Inspection Data
Appearance	brown viscous fluid
Odour	mild
Specific Gravity @ 15°C	0.940

PH @ 3% dilution	8.8
------------------	-----

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.