

Revolution Oil Limited Dagnall Road Great Gaddesden Hemel Hempstead Hertfordshire HP1 3BP England

Tel: +44 (0) 1442 842999 Fax: +44 (0) 1442 842777

www.revolutionoil.co.uk

sales@revolutionoil.co.uk enquiries@revolutionoil.co.uk

Registered in England & Wales No.4356026

VAT Reg No.GB 815 3964 16

Technical Data Sheet

Dexron II ATF







Dexron II ATF

Gear & Transmission Oils

Description

Revolution Dexron II is an automatic transmission fluid manufactured from high quality base oils which incorporate viscosity index improvers, anti-wear agents, detergents, defoamers and special additives to provide the controlled frictional characteristics required of a Dexron II type fluid.

Application

Revolution Dexron II is designed for use in automatic transmissions of most passenger cars, buses, off-highway / construction and military equipment as well as in selected manual transmissions. It is also suitable as a power steering fluid in the appropriate vehicles.

Performance Level

- GM Dexron II
- Allison C 3
- Caterpillar TO-2

Benefits

- Universal ATF reduces product storage and handling costs
- Low foaming tendencies
- High temperature stability
- Cab be used as a power steering fluid

Typical Inspection Data

	Units	Inspection Data
Brookfield Viscosity -40 °C	Pa.s	50,000cP max
Specific Gravity 15.6°C	Kg/m³	0.883
Kinematic Viscosity 100°C	mm²/s	6.8
Copper Corrosion		Nil
Flash Point	°C	210

^{**}In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.**

Updated: 12th November 2014 Page 2 of 2 Dexron II ATF