

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Supreme 20w/50

Supreme 20w/50

Engine Oils

Description

Revolution Supreme 20w/50 is a mixed fleet engine lubricant.

Application

Revolution 20w/50 Supreme is used in four stroke, normally aspirated and turbocharged diesel engines operating under moderate to heavy duty conditions. It can also be used in passenger cars and vans with normally aspirated or turbocharged gasoline, LPG or diesel engines.

Revolution 20w/50 Supreme can also be used as an engine lubricant in commercial vehicles, buses, off highway or military equipment.

Performance Level

- ACEA A2/B2/E2
- API CF-4/SJ/CF

Benefits

- Moderate drain interval
- protects against corrosion and rust
- Universal engine/transmission lubricant for buses, off highway and military equipment
- Good cold start qualities
- Protects against engine wear

Typical Test Data

	Units	Inspection Data
Viscosity Grade SAE		20w/50
Absolute Density 15°C		891
Kinematic Viscosity 100°C	mm ² /s	18.87
Kinematic Viscosity 40°C	mm ² /s	171.8
Viscosity Index		124
Total Base Number	mgKOH/g	8.5
Pour Point	°C	-18
Apparent Viscosity -15	mPa.s	8200

Sulphated Ash Content	%mass	1.11
Flash Point	°C	>200

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.