

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Jacobi 5w/30

Jacobi 5w/30

Semi Synthetic Engine Oils

Description

Jacobi is a semi Synthetic 5w/30 engine oil manufactured from a balanced blend of top quality mineral and synthetic base stocks, producing high quality engine oil. Its naturally higher lubricity offers lower internal friction for reduced engine wear. Its low viscosity offers improved flow rates and hydraulic tappet performance during cold start and engine idling. It offers excellent stay in grade performance for modern multi-valve engines.

Application

Jacobi 5w/30 is suitable for normally aspirated and turbocharged, petrol and diesel vehicles. It meets many of the latest Ford requirements. It is miscible with all synthetic and mineral based engine oils.

Performance Level

- ACEA A1/B1
- API SL/SJ/CF
- Ford WSS M2C 913-B
- BMW LL-FE-01
- Opel Pass
- ILSAC GF-2

Benefits

- Meets and surpasses the earlier specifications of WSS M2C 912 A1 and 913A.
- Extended drain capability
- Excellent low temperature stability for improved flow rates
- Improved fuel efficiency
- Semi-synthetic formulation

Typical Test Data

	Units	Inspection Data
--	-------	-----------------

Viscosity Grade SAE		5w/30
Specific Gravity 15°C		
0.875		
Kinematic Viscosity 100°C	mm ² /s	11.40
Kinematic Viscosity 40°C	mm ² /s	69.02
Viscosity Index		159
Total Base Number	mgKOH/g	8.89
Pour Point	°C	-38
Flash Point	°C	225

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.