

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

75w/90 Semi Synthetic Gear Oil

75w/90 Semi Synthetic Gear Oil

Gear & Transmission Oils

Description

Revolution semi synthetic EP 75w/90 is a high performance heavy duty automotive gear oil. It offers higher levels of performance when compared to straight mineral oils whilst being compatible with mineral oils. Revolution 75w/90 semi synthetic has excellent load carrying capacity, which is essential for shock load, high torque and high speed service operation. Extended drain intervals are enabled due to high thermal stability.

Application

For use in high performance manual transmissions, spiral bevel axles, high load drive axles, hypoid axles and steering units. The use of this product will often smooth and improve manual gear changes. This product is suitable for some light and heavy duty commercial vehicles and off highway applications.

Performance Level

- API GL5/GL4

Benefits

- Long service life
- Exceptional wear and protection
- Smoother gear shift
- Outstanding thermal stability

Typical Test Data

| | Units | Inspection Data |
|---------------------------|--------------------|-----------------|
| Absolute Density 20°C | Kg/m ³ | 0.865 |
| Appearance | | red |
| Kinematic Viscosity 100°C | mm ² /s | 14.5 |
| Kinematic Viscosity 40°C | mm ² /s | 94 |
| Viscosity Index | | 160 |
| Flash Point | °C | 220 |

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.