

Revolution Oil Limited Dagnall Road Great Gaddesden Hemel Hempstead Hertfordshire HP1 3BP England

Tel: +44 (0) 1442 842999 Fax: +44 (0) 1442 842777

www.revolutionoil.co.uk

sales@revolutionoil.co.uk enquiries@revolutionoil.co.uk

Registered in England & Wales No.4356026

VAT Reg No.GB 815 3964 16

Technical Data Sheet

Flushing Oil





Technical Data Sheet

Flushing Oil

Mineral Based Engine Oils

Description

An excellent quality Flushing Oil designed primarily for use as a Crankcase Flushing Fluid petrol and diesel engines prior to replenishment with new oil. Revolution Flushing Oil is a low viscosity flushing oil manufactured from solvent refined base oil and proprietary additives providing anti-wear, anti-corrosion, anti-oxidant and detergency/dispersancy properties.

Application

This Flushing Oil suitable for all four stroke engines requiring a flushing charge to remove sludge, carbon build up, and to neutralise residual acidity.

Benefits

- Fast one step operation
- Excellent cleaning action
- Removes black sludge
- Protects the engine as it cleans

Typical Inspection Data

| Kinematic Viscosity @ 40° (cSt) | 28.1 |
|--|---------|
| Kinematic Viscosity @ 100° (cSt) | 4.93 |
| Viscosity Index | 97 |
| Pour Point Degrees Centigrade | -12 |
| Flash Point Degrees Centigrade | 205 |
| Specific Gravity @ 15.6 Degrees Centig | ra.0676 |

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.