

Revolution Oil Limited Dagnall Road, Great Gaddesden Hemel Hempstead Hertfordshire HP1 3BP England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk www.q8oils.co.uk

sales@revolutionoil.co.uk enquiries@revolutionoil.co.uk

Registered in England & Wales No.4356026

VAT Reg No. GB 815 3964 16



Technical Data Sheet

Chainsaw Oil





Technical Data Sheet

Chainsaw Oil

Engine Oils

Description

Revolution Chainsaw oil has been specially developed from quality base oils using an adhesive agent to ensure that it is anti-fling.

Application

Revolution Chainsaw Oil is recommended for the lubrication of chains of all types of chainsaw. The adhesive agent enables the chain to stay in place in high pressure environments such as vibration, excessive G-forces, and physical removal by saw dust. The sprockets, link pins and rollers are also lubricated to protect against premature failure.

Benefits

- Excellent adhesion and anti-fling
- Lubricates and protects att parts of the chain linkage and drive
- Prolonged working life
- Reduces effects of high pressure working conditions

Typical Inspection Data

Kinematic Viscosity @ 40° (cSt)	150
Texture	stringy
Flash Point Degrees Centigrade	240
Density @ 15 Degrees Centigrade	886



Technical Data Sheet

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.