

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire

HP1 3BP England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk www.q8oils.co.uk

sales@revolutionoil.co.uk enquiries@revolutionoil.co.uk

Registered in England & Wales No.4356026

VAT Reg No. GB 815 3964 16



Technical Data Sheet

Gauss 0w/30 C2





Gauss 0w/30 C2

Low SAPS Fully Synthetic Engine Oils

Description

Gauss 0w/30 is fully synthetic Low Saps, high quality engine oil formulated to meet the demands of modern passenger car engines. Gauss 0w/30 is made from high quality base stocks and performance enhancing additives. Thus ensuring excellent resistance to thermal breakdown, outstanding low temperature pumpability as well as protecting against engine wear and deposit formation.

Application

Gauss 0w/30 is suitable for use where the performance level for PSA B71 2314 is required.

Performance Level

- ACEA C2
- PSA B71 2312

Benefits

- Excellent performance and fuel efficiency
- Long service intervals
- Low temperature performance
- Excellent protection against wear, rust and corrosion

Typical Inspection Data

Kinematic Viscosity @ 40°C (cSt)	54
Kinematic Viscosity @ 100°C (cSt)	9.7
Viscosity Index	167
Density @ 15°C	0.844
Flash Point °C	200
Pour Point °C	-52
Total Base Number (mg KOH/g)	6.1

^{**}In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.**

Updated: 7th July 2020 Page 2 of 2 Gauss 0w/30 C2