

Revolution Oil Limited

Dagnall Road, Great Gaddesden Hemel Hempstead Hertfordshire HP1 3BP England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk www.q8oils.co.uk

sales@revolutionoil.co.uk enquiries@revolutionoil.co.uk

Registered in England & Wales No.4356026

VAT Reg No. GB 815 3964 16



Technical Data Sheet

Alpha 5w/30 C3/C2





Alpha 5w/30 C3/C2

Low SAPS Fully Synthetic Engine Oils

Description

Revolution Alpha 5w-30 is an ultra high performance SAE 5W-30 synthetic engine oil for normal and extended drain intervals. This oil has been developed to enable outstanding performance along with full compatability with emission control and after treatment systems.

Application

Revolution Alpha 5w-30 is an engine oil designed for passenger cars and commercial vehicles with normally aspirated or turbo-charged gasoline, LPG or diesel Euro V and Euro VI engines requiring low SAPS engine oil.

Performance Level

- ACEA C3
- ACEA C2 suitable for use
- API SN/CF
- VW 502.00/505.01
- MB 229.52
- BMW Longlife-04
- GM Dexos 2
- FORD M2C 917-A
- RENAULT RN0700/0710

Updated: 15th January 2021 Page 2 of 3 Alpha 5w/30 C3/C2





Benefits

- Fuel efficiency
- Low SAPS formulation protecting Exhaust Catalyst and Diesel Particulate Filter
- Excellent engine cleanliness and wear protection increasing engine durability
- Extended drain interval capability
- Excellent high and low temperature performance
- Oxidation stability

Typical Test Data

	Units	Inspection Data
Viscosity Grade SAE		5w/30
Kinematic Viscosity 100°C	mm²/s	11.8
Kinematic Viscosity 40°C	mm²/s	68.6
Viscosity Index		165
Pour Point	°C	-32
Flash Point	°C	210
Sulphated Ash Content	%mass	0.79

^{**}In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.**

Updated: 15th January 2021 Page 3 of 3 Alpha 5w/30 C3/C2