

Revolution Oil Limited Dagnall Road, Great Gaddesden Hemel Hempstead Hertfordshire HP1 3BP England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk www.q8oils.co.uk

sales@revolutionoil.co.uk enquiries@revolutionoil.co.uk

Registered in England & Wales No.4356026

VAT Reg No. GB 815 3964 16



Technical Data Sheet

Epsilon 5w/30 VW





Technical Data Sheet

Epsilon 5w/30 VW

Low SAPS Fully Synthetic Engine Oils

Description

Revolution Epsilon 5w/30 is a fully synthetic long life low SAPs passenger car engine oil for normal and extended drain intervals. This oil has been developed to provide outstanding performance in terms of engine cleanliness and fuel economy along with effective emission control. Low SAPs additive technology ensures high level pollution control thereby minimising environmental damage.

Application

Revolution Epsilon 5w/30 is specially formulated for Volkswagen passenger car gasoline and diesel engines meeting VW 504.00-507.00 requirements. In addition Epsilon 5w/30 is suitable for a wide range of passenger car and light commercial vehicles including Honda, Hyundai, Kia, Nissan, Subaru and Toyota.

Revolution Epsilon 5w/30 is backward compatible with most other VW specifications.

Performance Level

- ACEA C3
- VW 504.00 level/507.00 level
- API SN/CF
- MB 229.51
- BMW Longlife-04
- Porsche C30

Benefits

- Lubricant designed for VW passenger car gasoline and diesel engines for Euro IV models.

- Backwards compatible with most VW gasoline engines and diesel engines with or without pump injectors.

- Extended drain interval capability compatible with flexible ODI systems.
- High oil film strength under all engine operating conditions.



Technical Data Sheet

- Excellent engine performance at all driving conditions.
- Outstanding protection against foam formation, rust and corrosion.

Typical Inspection Data

	Units	Inspection Date
Viscosity Grade SAE		5w/30
Kinematic Viscosity 100	ୁ rû m²∕s	11.8
Kinematic Viscosity 40°	0mm²/s	77
Viscosity Index		160
Sulphated Ash	%mass	0.6
Pour Point °C		-45
TBN (mgKOH/g)		8.00
Flash Point	°C	200

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.