

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

75w/90 Fully Synthetic Gear Oil

75w/90 Fully Synthetic Gear Oil

Gear & Transmission Oils

Description

Revolution 75w/90 fully synthetic gear oil is a high performance product manufactured from a blend of synthetic oils, shear stable viscosity index improvers and a multipurpose extreme pressure additive system. Revolution fully synthetic 75w/90 is manufactured from high quality hydrocarbon base stocks with a high viscosity index ensuring that the oil demonstrates outstanding load capacity, high torque and high speed. The high thermal stability of this products components allow extended drain intervals to be realised and the levels of protection provided ensure maximum component durability.

Application

For use in high performance manual transmissions, spiral bevel axles, high load drive axles, hypoid axles, transfer boxes and other transmission equipment found in passenger cars, light and heavy duty commercial vehicles.

Performance Level

- API GL5, GL4

Benefits

- Very high levels of rust and corrosion resistance
- Excellent oxidation stability
- Very good thermal stability
- Outstanding low and high temperature performance
- Long service life
- Maximum component protection

Typical Test Data

	Inspection Data
Specific Gravity 15.6°C	0.868
Appearance	red
Viscosity Index	155
Kinematic Viscosity 100°C	15.5
Kinematic Viscosity 40°C	105.8
Flash Point °C	220
Brookfield Viscosity -40°C	38,000

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.