

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

CVT Fluid Fully Synthetic

CVT Fluid Fully Synthetic

Gear & Transmission Oils

Description

Revolution CVT Fluid is a high performance, fully synthetic transmission fluid developed for continuously variable transmission (CVT) equipped passenger vehicles. The specialised performance additive package has demonstrated equal, and in many cases better, performance than most OEM supplied fluids in areas such as wear and protection.

Application

Revolution CVT Fluid is recommended for use in a wide range of passenger cars vehicles fitted with continuously variable transmissions.

(Revolution CVT Fluid should not be used in conventional automatic transmissions, DCT/DSG transmissions, manual transmissions or Toyota e-CVT (this is the Toyota Hybrid System).)

Performance Level

- Audi/VW TL52180, G052 516, G052 180 A1/A2/A6
- Ford CVT30/Mercon C, CVT 23, WSS-M2C933-A
- Honda HMMF, HCF-2
- Toyota/Lexus TC
- Nissan NS1, NS-2
- Mitsubishi CVTF-J1
- Mazda CVTF 3320
- Subaru NS-2/Lineartronic CVTF, K04525Y0710, CV-30, e-CVTF
- Mini Cooper EZL 799, EZL 799A, ZF CVT V1
- Kia/Hyundai SP-CVT 1
- Suzuki CVTF 3320, TC/NS-2/CVT Green 1
- Dodge/Jeep NS-2, CVTF+4, MOPAR CVT 4
- GM/Saturn DEX-CVT
- Mercedes-Benz 236.20, CVT 28

- Renault Elfmatic
- BMW 8322 0136 376, 8322 0 429 154 (EZL799, EZL 799A)

This CVT Fluid is also suitable for use out of warranty where the following performance levels are specified:

- Nissam NS-3
- GM/Saturn CVTF I-Green 2
- Suzuki CVTF Green 2
- Toyota/lexus FE

Benefits

- Excellent wear protection
- Low temperature fluidity
- Low foaming
- Excellent resistance to oxidation
- Outstanding shear stability
- Anti shudder durability

Typical Inspection Data

| | |
|------------------------------------|-------------|
| Appearance | Amber/Clear |
| Kinematic Viscosity 40°C c(St) | 33.7 |
| Kinematic Viscosity 100°C (cSt) | 7.2 |
| Viscosity Index | 185 |
| Flash Point | -48 |
| Pour Point | 200 |
| Brookfield Viscosity @ -40 °C (cP) | 9020 |

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.