

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Kepler Monograde Engine Oils

Kepler Monograde Engine Oils

Engine Oils

Description

Kepler Monograde Engine Oils are manufactured from high quality base oils and carefully selected additives. They are developed in many viscosities to suit an array of applications. These oils are suitable for normally aspirated and turbo charged diesel engines and petrol engines in passenger cars, light and heavy commercial vehicles, plant, compressor, industrial and certain hydraulic and transmission applications. They are miscible with all synthetic and mineral based engine oils.

Performance Level

- API CD/SF
- CCMC G2/D2
- CATERPILLAR SERIES 3 & TO-2
- ALLISON C-3
- MIL-L-2104C

Benefits

- Suitable for mixed fleet applications
- Available in various viscosities
- Cost effective

Typical Inspection Data

		10W	20W	30	40	50
SAE Viscosity Grade		10	20	30	40	50
Kinematic Viscosity 40°C	mm ² /s	35.71	60.0	98.02	142.0	234.0
Kinematic Viscosity 100°C	mm ² /s	5.81	8.13	11.05	14.8	20.57
Viscosity Index		103	103	105	104	103
Specific Gravity 15 degrees	°C	0.880	0.884	0.887	0.888	0.890
Flash Point	°C	212	215	219	220	225
TBN (mgKOH/g)		5.08	5.12	5.09	5.07	5.11

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.