

Revolution Oil

A New Generation of Lubricants

Revolution Oil Limited
Dagnall Road
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999
Fax: +44 (0) 1442 842777

www.revolutionoil.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No.GB 815 3964 16

Technical Data Sheet

Uniclear 15w/40



Uniclear 15w/40

Mineral Based Engine Oils

Description

Uniclear 15w/40 SL/CH4 is a high performance multigrade engine oil, meeting the latest API classifications. Present day motor engineering and motoring conditions have necessitated the rapid advancement in lubricant design and performance.

Uniclear 15w/40 SL/CH4 is a new generation multigrade engine oil manufactured from carefully selected base oils and the very latest additive technology. It meets the majority of the latest engine manufacturers requirements and specifications. It can be confidently supplied for most mixed fleet applications. Superior dispersant additives help maintain engine cleanliness and the latest detergent additives help reduce unwanted deposits in turbo charges and on pistons.

Benefits

- High shear stability for stay in grade performance
- Excellent high temperature stability
- Improved bore polishing protection
- Excellent anti wear performance for reduced engine wear
- Ideal mixed fleet lubricant
- Excellent sludge control for stop-go city motoring

Application

Uniclear 15w/40 SL/CH4 is suitable for normally aspirated and turbo charged highly stressed petrol engines and diesel engines in the passenger cars and heavy commercials, vans, plant, buses and industrial equipment. It is miscible with all synthetic and mineral based engine oils.

Specification

- API SL/CH4
- ACEA A3/B3/B4/E2
- VW 505
- MB 228.1 AND 229.1
- MACK EO-L
- MAN 271
- MTU TYPE 1

- VOLVO VDS

Typical Inspection Data

Specific Gravity @ 15.6 degrees centigrade	0.886
Kinematic Viscosity @ 100 degrees centigrade	14.25
Kinematic Viscosity @ 40 degrees centigrade	104.9
Viscosity Index	139
Flash Point degrees centigrade	215
Pour Point degrees centigrade	-30
TBN (mgKOH/g)	10.2

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.