

Revolution Oil

A New Generation of Lubricants

Revolution Oil Limited
Dagnall Road
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999
Fax: +44 (0) 1442 842777

www.revolutionoil.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No.GB 815 3964 16

Technical Data Sheet

Delta 5w/40 C3



Delta 5w/40 C3

Low SAPS Fully Synthetic Engine Oils

Description

Revolution Delta 5w-40 is a long life, fully synthetic low SAPS SAE 5w-40 passenger car engine oil for normal and extended drain intervals.

Application

Revolution Delta 5w-40 an engine oil developed to enable outstanding performance along with full compatibility with on board emissions systems and DPFs. This ensures minimal pollution to the environment.

Performance Level

- API SN/CF
- ACEA C3
- MB 229.51
- BMW LL-04
- VW 502.00/505.01
- Porsche A40
- GM Dexos 2
- Ford WSS-M2C917-A
- Renault RN0700/RN0710
- Fiat 9.55535-S2

Benefits

- Viscosity remains stable during total service of the oil for optimum engine protection
- Lubricant suitable for MB passenger car gasoline and diesel engines for Euro IV and Euro V models
- Low SAPS engine oil protects exhaust gas after-treatment system
- Reduces fuel consumption
- Extended drain interval capability

- High oil film strength under all engine operating conditions
- Excellent engine performance at all driving conditions
- Outstanding protection against foam formation, rust and corrosion

Typical Inspection Data

Kinematic Viscosity @ 40°C (cSt)	85.3
Kinematic Viscosity @ 100°C (cSt)	14.2
Viscosity Index	169
Sulphated Ash Content % (weight)	0.78
TBN (mg KOH/g)	7.2
Pour Point (°C)	-38
Flash Point (°C)	225

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.