

# Revolution Oil

**A New Generation of Lubricants**

Revolution Oil Limited  
Dagnall Road  
Great Gaddesden  
Hemel Hempstead  
Hertfordshire  
HP1 3BP  
England

Tel: +44 (0) 1442 842999  
Fax: +44 (0) 1442 842777

[www.revolutionoil.co.uk](http://www.revolutionoil.co.uk)

[sales@revolutionoil.co.uk](mailto:sales@revolutionoil.co.uk)  
[enquiries@revolutionoil.co.uk](mailto:enquiries@revolutionoil.co.uk)

Registered in England & Wales  
No.4356026

VAT Reg No.GB 815 3964 16

## Technical Data Sheet

Epsilon 5w/30 VW



## Epsilon 5w/30 VW

### Low SAPS Fully Synthetic Engine Oils

#### Description

Revolution Epsilon 5w/30 is a fully synthetic long life low SAPs passenger car engine oil for normal and extended drain intervals. This oil has been developed to provide outstanding performance in terms of engine cleanliness and fuel economy along with effective emission control. Low SAPs additive technology ensures high level pollution control thereby minimising environmental damage.

#### Application

Revolution Epsilon 5w/30 is specially formulated for Volkswagen passenger car gasoline and diesel engines meeting VW 504.00-507.00 requirements. In addition Epsilon 5w/30 is suitable for a wide range of passenger car and light commercial vehicles including Honda, Hyundai, Kia, Nissan, Subaru and Toyota.

Revolution Epsilon 5w/30 is backward compatible with most other VW specifications.

#### Performance Level

- ACEA C3
- VW 504.00 level/507.00 level
- API SN/CF
- MB 229.51
- BMW Longlife-04
- Porsche C30

#### Benefits

- Lubricant designed for VW passenger car gasoline and diesel engines for Euro IV models.
- Backwards compatible with most VW gasoline engines and diesel engines with or without pump injectors.
- Extended drain interval capability compatible with flexible ODI systems.
- High oil film strength under all engine operating conditions.
- Excellent engine performance at all driving conditions.

- Outstanding protection against foam formation, rust and corrosion.

## Typical Inspection Data

	Units	Inspection Data
Viscosity Grade SAE		5w/30
Kinematic Viscosity 100°C	mm <sup>2</sup> /s	11.8
Kinematic Viscosity 40°C	mm <sup>2</sup> /s	77
Viscosity Index		160
Sulphated Ash	%mass	0.6
Pour Point °C		-45
TBN (mgKOH/g)		8.00
Flash Point	°C	200

\*\*In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.\*\*