

# Revolution Oil

**A New Generation of Lubricants**

Revolution Oil Limited  
Dagnall Road  
Great Gaddesden  
Hemel Hempstead  
Hertfordshire  
HP1 3BP  
England

Tel: +44 (0) 1442 842999  
Fax: +44 (0) 1442 842777

[www.revolutionoil.co.uk](http://www.revolutionoil.co.uk)

[sales@revolutionoil.co.uk](mailto:sales@revolutionoil.co.uk)  
[enquiries@revolutionoil.co.uk](mailto:enquiries@revolutionoil.co.uk)

Registered in England & Wales  
No.4356026

VAT Reg No.GB 815 3964 16

## Technical Data Sheet

Beta 5w/30 C4



## Beta 5w/30 C4

### Low SAPS Fully Synthetic Engine Oils

#### Description

Revolution Beta 5w/30 is a Long Life Ultra High Performance Low SAPS synthetic engine oil that has been developed for the latest Renault Euro 5 engines equipped with a DPF.

Revolution Beta 5w/30 is an ultra high performance SAE 5W/30 synthetic engine oil. Beta 5w/30 has been developed to enable outstanding performance along with effective emissions control. Low Saps additive technologies ensure optimum performance of emission control equipment including DPFs.

#### Application

Revolution Beta Long Life 5w/30 has been designed for Renault passenger car and commercial vehicle engines requiring a Low SAPS oil. It is capable of extended drain intervals. Revolution Beta 5w/30 is suitable for Renault Euro 5 diesel engines equipped with a DPF requiring the RN 0720 engine oil specification and is the only product suitable for Euro 5 Renault engines requiring a Low SAPS product.

#### Performance Level

- ACEA C4
- MB 226.51
- Renault RN 0720

#### Benefits

- Reduces fuel consumption
- Low SAPS formulation protects Exhaust Catalyst and Diesel Particulate Filter
- Excellent engine cleanliness and wear protection that increases engine durability
- Outstanding high and low temperature performance
- Fuel efficiency
- Extended drain intervals

#### Typical Inspection Data

	Units	Inspection Data
Viscosity Grade SAE		5w/30
TBN mg KOH/g		6.0
Kinematic Viscosity 100°C	mm <sup>2</sup> /s	11.8

Kinematic Viscosity 40°C	mm <sup>2</sup> /s	67.3
Viscosity Index	% wt	173
Pour Point	°C	-45
Flash Point	°C	212

\*\*In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.\*\*