

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Super Universal Tractor Oil
15w/30

Super Universal Tractor Oil 15w/30

Universal Oils

Description

Super Universal Tractor Oil (SUTO) is designed to cover virtually all the lubrication requirements of agricultural machinery including farm tractors. It provides excellent high and low temperature stability, high standards of engine cleanliness and good oxidation resistance. Its natural high lubricity offers lower internal friction for reduced engine wear.

Application

Engine oil: SUTO 15w/30 is suitable for all four stroke, naturally aspirated and turbocharged diesel engines and four stroke petrol engines.

Hydraulic oil: SUTO 15w/30 has good oxidation resistance, thermal stability and low temperature performance.

Transmission oil: SUTO 15w/30 has been primarily formulated to be used in farm tractors and other plant where the transmission contains oil immersed "wet" brake systems.

Benefits

- Natural high lubricity
- Good anti-foaming and air release properties
- Excellent Anti-wear Protection
- Helps reduce wet brake noise
- Suitable for most agricultural machinery requirements

Performance Level

- API CE/SF
- API GL4
- Mil-I-2104D
- CCMC D4
- DB 227.1

- DB 228.1
- Caterpillar Series 3
- ZF TE-ML-06 + 07
- MIL-L-2105
- Ford M2C 159 B2
- Ford ESE-N2C-86A/B
- ESN-86A/B
- M2C 134D
- Massey Ferguson M1139, M1135, M1127a
- John Deere J20A, JD 303, J14B and JDM-J27A
- Case MS 1206
- IH B6
- Allison C4
- API GL4 (L-20)

Typical Inspection Data

Kinematic Viscosity @ 100 degrees centigrade	114
Kinematic Viscosity @ 40 degrees centigrade	62
Viscosity Index	129
Flash Point degrees centigrade	212
Pour Point degrees centigrade	30
Sulphated Ash %	1.5
TBN (mgKOH/g)	10

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.