

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Fully Synthetic ATF (MB
236.14)

Fully Synthetic ATF (MB 236.14)

Gear & Transmission Oils

Application

Revolution Fully Synthetic ATF is designed for use in 7-speed Mercedes-Benz automatic transmissions when MB236.14 is specified. It is also backwards compatible with MB 236.12. It can also be used in 5-speed automatic transmissions, type 722.6 with rear wheel drive.

Benefits

- Fuel economy 
- Extended drain intervals
- Outstanding resistance against wear and extends transmission life
- Reduces sludge and varnish build up
- Good oxidation and thermal stability
- Outstanding frictional performance
- Improved shear stability for a stable viscosity during use
- Provides immediate lubrication after cold start
- Protection against rust and corrosion
- Outstanding elastomer compatibility

Performance Level

-
MB 236.14

-
MB 236.12

Typical Test Data

Kinematic Viscosity @ 40° (cSt)	29.5
---------------------------------	------

Kinematic Viscosity @ 100° (cSt)	6.4
Viscosity Index	185
Pour Point Degrees Centigrade	-51
Brookfield Viscosity -40 Degrees Centigrade	Centigrade
Flash Point Degrees Centigrade	>200
Density @ 15 Degrees Centigrade	847

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.