

# Revolution Oil

Revolution Oil Limited  
Dagnall Road,  
Great Gaddesden  
Hemel Hempstead  
Hertfordshire  
HP1 3BP  
England

Tel: +44 (0) 1442 842999

[www.revolutionoil.co.uk](http://www.revolutionoil.co.uk)  
[www.q8oils.co.uk](http://www.q8oils.co.uk)

[sales@revolutionoil.co.uk](mailto:sales@revolutionoil.co.uk)  
[enquiries@revolutionoil.co.uk](mailto:enquiries@revolutionoil.co.uk)

Registered in England & Wales  
No.4356026

VAT Reg No. GB 815 3964 16

**Q8 Oils**  
*authorised distributor*

## Technical Data Sheet

### 75w/80 Semi Synthetic Gear Oil

## 75w/80 Semi Synthetic Gear Oil

### Gear & Transmission Oils

#### **Description**

Revolution semi synthetic 75w/80 is a high performance heavy duty automotive gear oil. This gear oil is manufactured from high quality base oils and high levels of extreme pressure additives to provide a lubricant with outstanding wear protection. This product offers exceeds the performance of other GL4/5 products in terms of synchroniser performance, thermal and oxidation stability, shift quality and fuel efficiency.

#### **Application**

For use in high performance manual transmissions, spiral bevel axles, high load drive axles, hypoid axles and steering units. The use of this product will often smooth and improve manual gear changes. This product is also suitable for synchromesh gearboxes. This 75w/80 is recommended for use in a wide variety of manual transmissions in passenger cars and vans that are out of vehicle warranty. This product is also recommended with the performance level of MTF94 is required.

This product is suitable for:

BMW, Citroen, Alfa Romeo, VW, Mini, Peugeot, Fiat, Seat, Mercedes, Renault, Volvo, Skoda, Smart, Dacia, Honda and Vauxhall.

#### **Performance Level**

- API GL5
- API GL4

#### **Benefits**

- Long service life
- Smoother gear shift
- Exceptional wear and protection
- Thermal and oxidation stability
- seal compatibility
- Corrosion protections
- Pitting resistance

### Typical Test Data

|                               |        |
|-------------------------------|--------|
| SAE Viscosity                 | 75w/80 |
| Appearance                    | red    |
| Kinematic Viscosity @ 40°     | 58.0   |
| Viscosity Index               | 136    |
| Flash Point °C                | 220    |
| Kinematic Viscosity @ 100°    | 9.1    |
| Pour Point Degrees Centigrade | -45    |
| Specific Gravity @ 20 °C      | 0.875  |

\*\*In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.\*\*