

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Green Long Life Antifreeze

Green Long Life Antifreeze

Antifreeze

Description

Green Long Life Antifreeze is an engine coolant concentrate based on ethylene glycol. It contains a hybrid corrosion inhibitor package with salts of organic acids and silicates. Green Long Life Antifreeze is free of nitrites, amines and phosphates.

Green Long Life Antifreeze was developed to protect car, truck and bus engines of both ferrous and aluminium construction against corrosion and frost damage. It contains a blend of inhibitors designed to give a high degree of corrosion protection to engine components such as radiators, cylinder blocks/heads and water pumps.

Performance Level

- ASTM D 3306
- BS 6580 (1992)
- BMW N 600 69.0
- German Army TL 6850-0038/1
- KHD H-LV 0161 0188
- MAN 324-NF
- MERCEDES BENZ DBL 7700.20
- MTU MTL 5048
- OPEL/GM B 040 0240
- SAAB 6901599
- VW/AUDI/SEAT/SKODA TL 774-C

Typical Inspection Data

	Method	
Appearance	Visual	Green
Density at 20 degrees centigrade	DIN 51 757/4	1.121-1.123
Boiling Point degrees centigrade	ASTM D 1120	=>165
Freezing Point degrees centigrade(50% dilution by water)	ASTM D 1177	-38
PH (50% volume)	ASTM D 1287	7.1-7.3

Reserve Alkalinity M/10 HCl	ASTM D 1287	13-15ml
Water Content	ASTM D 1123	3.5%
Foaming Properties	ASTM D 1881	50 (vol ml)1 (break)

Dilution Strength Freezing Point

33%	-18 degrees centigrade
50%	-38 degrees centigrade

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.