

# Revolution Oil

Revolution Oil Limited  
Dagnall Road,  
Great Gaddesden  
Hemel Hempstead  
Hertfordshire  
HP1 3BP  
England

Tel: +44 (0) 1442 842999

[www.revolutionoil.co.uk](http://www.revolutionoil.co.uk)  
[www.q8oils.co.uk](http://www.q8oils.co.uk)

[sales@revolutionoil.co.uk](mailto:sales@revolutionoil.co.uk)  
[enquiries@revolutionoil.co.uk](mailto:enquiries@revolutionoil.co.uk)

Registered in England & Wales  
No.4356026

VAT Reg No. GB 815 3964 16

**Q8 Oils**  
*authorised distributor*

## Technical Data Sheet

### Dexron III ATF

## Dexron III ATF

### Gear & Transmission Oils

#### Description

Revolution Dexron III is a multi purpose automatic transmission fluid for commercial and passenger car gearboxes meeting a wide range of performance levels. This product is manufactured from premium synthetic base stocks and high quality solvent refined base oils. The specially selected additives and friction modifiers produce a durable transmission fluid, with a prolonged product life under the most severe conditions.

This product is dyed red to help prevent mis-application in engines.

#### Application

Revolution Dexron III is recommended for use in automatic transmissions of passenger cars, trucks and buses where Dexron IID, Dexron III and Ford Mercon fluids are specified.

#### Performance Level

- GENERAL MOTORS DEXRON IIIH,IIIG
- GENERAL MOTORS DEXRON IID
- FORD MERCON
- ALLISON C-4, TES-389
- MERCEDES BENZ 236.1, 236.9, 236.7, 236.6, 236.5, 236.10
- MAN 339F, 339 V1&Z1, 339 V2 & Z2
- ZF TE-ML 02F, 03D, 04D, 09, 11A, 11B, 14A, 14B, 16L, 17C
- VOITH DIWA & MIDIMAT (G607) 55.6335, 55.6336
- VOLVO 97341, 97340
- CATERPILLAR TO-2

#### Benefits

- Constant frictional performance
- Excellent oxidation stability
- High temperature operation stability

- Outstanding wear protection and component life
- Low temperature fluidity
- Can be used as a power steering fluid
- Compatibility with all elastomers and other sealing materials

### Typical Inspection Data

	Units	Inspection Data
Density 156 °C	Kg/m <sup>3</sup>	0.882
Kinematic Viscosity 100°C	m <sup>2</sup> /s	8.32
Flash Point °C		205
Appearance		Red

\*\*In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.\*\*