

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Dexron VI Synthetic Automatic Transmission Fluid

Dexron VI Synthetic Automatic Transmission Fluid Gear & Transmission Oils

Description

Dexron VI is an high quality, fully synthetic automatic transmission fluid formulated primarily for applications that require the GM Dexron VI specification. This product has many advantages over more traditional ATFs such as improved shear stability, excellent wear control and extended fluid life.

Application

Dexron Vi is recommended for step type automatic transmissions and power steering units in cars, vans, trucks, buses, agricultural and industrial engines.

Performance Level

- GM Dexron VI
- Dexron IIIH, IIIG, IID, TASA
- JASO 1A
- Allison C-4
- Caterpillar TO-2
- Mercedes-Benz 236.5
- Voith 55.6335 (formerly G607)
- Volvo 97340
- ZF TE-ML 09

Application

In addition to the above, Dexron VI is recommended for service fill in the following applications:

- AISIN WARNER JWS 3309, JWS 3324, T IV
- FIAT (ALL VEHICLES), TYPO T IV
- SAAB T IV (JWS 3309)
- AS 68 RC (T IV)
- HONDA / ACURA Z-1, PREMIUM
- SATURN T IV (JWS 3309)
- AUDI 5 HP LT 71141 (ZF 5 HP 18FL / 19FL / 24A)
- HYUNDAI/ KIA SP II, SP III, SP IV & HYUNDAI SPH-IV
- SCION (ALL VEHICLES)
- AUDI 5 HP LT 71141 (AUDI G-052-162-A1 / A2)
- NISSAN / INFINITY MATIC D, MATIC J, MATIC K, MATIC S
- SHELL M 115
- AUDI 5 HP (ZF 5 HP 30)
- ISUZU BESCO ATF II, ATF III
- SUBARU ATF, ATF HP
- AUDI G-055-025-A2 (JWS 3309)
- JAGUAR ATF 3403 M115, LT 71141, JLM 20238 SUZUKI ATF 3309
- BMW ETL-7045, 7045E
- JWS 3309 (T IV)
- TEXACO ETL-7045E
- BMW LA2634
- JWS 3324 (WS)
- TEXACO ETL-8072B
- BMW 5 HP LT 71141 (ZF 5 HP 18FL / 19FL / 24A)
- MAZDA ATF M III
- TOYOTA TYPE T-III, T-IV (JWS 3309)
- BMW 5 HP (ZF 5 HP 30)
- MERCEDES BENZ ZF HP20, 236.1, 236.5, 236.6, 236.7, 236.8, 236.9

- TOYOTA WS (JWS 3324)
- BMW ETL-8072B
- MITSUBISHI DIAMOND SP II, SP III, SP IV
- VOLVO T IV (JWS 3309)
- BMW MINI JWS 3309
- NAG 1
- VW 5 HP LT 71141 (ZF 5 HP 18FL / 19FL / 24A)
- CHRYSLER/DODGE MOPAR AS 68 RC (T IV)
- OPEL (All Vehicles)
- VW 5 HP LT 71141(VW G-052-162-A1 / A2)
- DAEWOO LT 71141
- PEUGEOT ZF 4 HP20
- VW 5 HP (ZF 5 HP 30)
- ESSO LT 71141
- PORSCHE ATF 3403-M115, LT 71141, T IV (JWS 3309)
- VW G-055-025-A2(JWS 3309)

Benefits

- Extended fluid life
- Fuel economy
- Excellent low and high temperature stability
- Backwards compatible with previous GM Dexron specifications
- High film strength
- Low foaming
- Outstanding wear protection

Typical Inspection Data

Brookfield Viscosity @ -40°C (cP)	12,030
Kinematic Viscosity @ 100°C (cSt)	6.0
Appearance	red
Density @ 15.6 °C	0.845
Pour Point °C	-53
Flash Point (°C)	190

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.