

# Revolution Oil

Revolution Oil Limited  
Dagnall Road,  
Great Gaddesden  
Hemel Hempstead  
Hertfordshire  
HP1 3BP  
England

Tel: +44 (0) 1442 842999

[www.revolutionoil.co.uk](http://www.revolutionoil.co.uk)  
[www.q8oils.co.uk](http://www.q8oils.co.uk)

[sales@revolutionoil.co.uk](mailto:sales@revolutionoil.co.uk)  
[enquiries@revolutionoil.co.uk](mailto:enquiries@revolutionoil.co.uk)

Registered in England & Wales  
No.4356026

VAT Reg No. GB 815 3964 16

**Q8 Oils**  
*authorised distributor*

## Technical Data Sheet

0, 00, 000 EP Semi Fluid  
Grease

## 0, 00, 000 EP Semi Fluid Grease

### Greases

#### Description

A premium quality semi-fluid grease designed for centralised lubrication systems. Suitable for anti-friction and plain bearings subjected to high load conditions. Lithium 0/00/000EP can also be used for gearboxes designed to operate with a semi-fluid slumping grease.

#### Benefits

- Excellent extreme pressure and anti-wear performance
- High degree of corrosion protection
- Highly versatile semi-fluid grease for centralised lubrication

#### Application

Lithium 0/00/000 EP can be applied manually, or via a centralised lubricating system capable of pumping an NLGI No. 0/00/000 grease.

As with all greases used for the first time, check compatibility with the grease applied previously and if necessary purge bearings prior to application. Likewise, as a general rule, take care not to over-lubricate and apply the quantity of grease recommended by the bearing manufacturer.

#### Typical Inspection Data

	0	00	000
Appearance	Smooth Semi Fluid Grease		
Colour	Dark Brown		
NLGI classification	0	00	000
Thickener	Lithium Soap		
Base oil	Blend of solvent refined mineral oil		
Base oil viscosity @ 40C (IP71) cSt	180	180	180
Worked penetration (IP112)	355 - 385	400-430	445-475
Copper Corrosion (IP112)	pass	pass	pass
Resistance to corrosion EMCOR (IP220)	0:0	0:0	0:0
Four ball weld load (IP239) kgs	315	315	315
Timken OK load (IP326) lbs	50	50	50

---

Operating temperature range degrees centigrade	-30 to +110	-30 to + 110	-30 to +110
--	-------------	--------------	-------------

\*\*In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.\*\*