

Revolution Oil

Revolution Oil Limited
Dagnall Road,
Great Gaddesden
Hemel Hempstead
Hertfordshire
HP1 3BP
England

Tel: +44 (0) 1442 842999

www.revolutionoil.co.uk
www.q8oils.co.uk

sales@revolutionoil.co.uk
enquiries@revolutionoil.co.uk

Registered in England & Wales
No.4356026

VAT Reg No. GB 815 3964 16

Q8 Oils
authorised distributor

Technical Data Sheet

Pin and Bush Lube

Pin and Bush Lube

Greases

Description

Pin and Bush Lube is a tenacious grease designed for heavy duty applications where adhesion, shock loading and good corrosion protection is needed. It has been proven ideal for use on bucket pins and bushes on heavy earth moving equipment, crane slews, and also as an assembly and running in compound. The presence of graphite will fill surfaces and distribute load evenly preventing further wear and is therefore particularly suitable to extend the life worn components.

Benefits

- A high level of lubricating solids keeps working surfaces apart and substantially extends component life.
- Being fully resistant to the wet, extends the life of the lubricant and protects components from corrosion.
- Adhesion improvers provide increased lasting protection.

Application

PBL can be applied by hand, or by using a standard grease gun (400gm cartridges available). (Due to the high lubricating solids content, PBL is not recommended for use on anti-friction bearings.)

Typical Inspection Data

Appearance	Smooth grease
Colour	Black/Grey
NLGI classification	2.5
Thickener	Lithium Soap
Base oil	Blend of mineral oils
Worked penetration (IP50)	265-295
Dropping point (IP132) °C	185 min
Oil separation (IP121) %	5 max
Water washout (ASTM D1264) @ 39°C	3

Copper Corrosion (IP112)	Pass
Resistance to corrosion Emcor (a) (IP220)	0:0
Four Ball Weld Load (IP 239) kgs	700
Operating temperature range °C	-20 to +140
Solids %	16
Oxidation stability @ 100°C (IP142)	
Pressure drop after 100 hrs psi	4
Pressure drop after 400hrs psi	14

In line with our policy of continued improvement, Revolution Oil Ltd reserves the right to change specification and availability without prior notice. E and O E.